

ACCURL CNC PRESS BRAKE SMART-PRO B SERIES

The Smart-Pro S Series was designed and built to meet the small and medium-sized machining parts with extreme attention to speed, ergonomics and ease of use.



SPECIFICATIONS

Type	Bending Capacity KN	Bending Length mm	Distance between side frames mm	Opening height mm	Throat depth mm	Cylinder stroke mm	Main power kw	Oil volume L	Fast Approach Speed mm/s	Bending Speed mm/s	Return Speed mm/s	Length+/- mm	Width+/- mm	Height+/- mm	Weight+/- kg
B1330	300	1300	1050	350	200	150	3.0	100	160	16	170	2250	1500	2300	2800
B1535	350	1500	1200	350	200	150	3.7	200	160	16	170	2210	1500	2300	3300
B1540	400	1500	1200	350	200	150	3.7	200	160	16	170	2210	1500	2300	3300

STANDARD FEATURES

- Maximum productivity thanks to high speed levels
- Movement of the axis at extremely fast rate
- Low consumption with inverter
- Ergonomic design
- Compact dimensions
- Work area LED lighting
- Extremely quiet
- Possibility to customize tool clampings depending on customer requirements

STANDARD EQUIPMENT

- CNC ESA 640 or DELEM DA58T touch screen built into the central casing
- 150 mm stroke cylinders
- 350 mm opening
- Double guide of the beam
- X=450mm R=150mm back gauge stroke
- Lasersafe dual laser photocells
- High speed backgauge with ball screw movements
- 220 mm/s approaching speed
- 300 mm/s return speed
- Givi linear scales
- Voith pump
- Hoerbiger hydraulic system
- Electrical cabinet with Telemecanique-Schneider, Abb and Esautomation components
- High efficiency IE3 class engine
- Start/stop function



DELEM DA58T CNC Touch Screen



Work area, LED lighting



Built-in pedals